



# TILEPRO

## Tile Adhesive



### TECHNICAL SPECIFICATIONS: US ISO: 13007 - 1

- ▶ Initial setting: 6hrs
- ▶ Final setting: 24hrs
- ▶ Correction time: 25min
- ▶ Open time: 15min
- ▶ Pot life: 2 - 2.5hrs

### STORAGE

Promix TilePro should be stored in a dry place.

### STORAGE

12 months from the date of manufacturing.

### PRECAUTIONS

- Though it contains non-toxic materials, care should still be taken to avoid dust inhalation while mixing and handling. In case of contact with eyes or mouth, wash with plenty of clean water.
- Keep it in a dry place out of reach of children.
- Persons who are allergic to cement/cement products should take proper precautions before use.
- We recommend to use protective hand gloves and nose mask.
- Do not mix with sand, cement or any other materials.

### STORAGE

Promix TilePro should be stored in a dry place.

### SHELF LIFE

12 months from the date of manufacturing.

### MANUFACTURED & PACKAGED BY PROMiX MANUFACTURING CO. LTD.

Shop No. 118, Hardware City, Nakasero  
P.O Box 114654, Kampala Uganda.

+256(0) 777 468467 | 704 659146

operations@promixworld.com

promixworld.com



# TILEPRO

## Tile Adhesive

### ABOUT US

Promix is Uganda's pioneer manufacturing company that makes white / Grey-cement-based premixed mortars, for building construction and renovation products. The product range is wide with impeccable quality & competitive pricing. We are committed to continually offering you the best innovative ready-to-use building materials that will make your construction projects better, faster and economical. All our materials are tested and approved by the Uganda National Bureau of Standards (UNBS). They are expertly prepared and packaged with modern high-tech machinery.

### OUR PRODUCTS

#### TILEPRO ADHESIVE - IMPROVED STRENGTH

Normal cementitious tile adhesive is ready mixed high strength cement base tile adhesive for fixing of wall and floor tiles onto substrates of rendering and screed.

**NOTE:** This works for Ceramic Wall and Floor tiles.

#### TILEPRO ADHESIVE - DOUBLE STRENGTH

Normal cementitious tile adhesive is ready mixed high strength cement base tile adhesive for fixing of wall and floor tiles onto substrates of rendering and screed.

**NOTE:** This works for Porcelain, Granite, and other Non-Porous tiles.

#### STONEPRO - TRIPLE STRENGTH

Triple strength cementitious tile adhesive is ready mixed high strength cement base tile adhesive for fixing for wall and floor tiles onto substrates of rendering and screed.

**NOTE:** This works for Marble, Granite, Travertine, White Porcelain and Stone.



### HOW TO USE TILEPRO ADHESIVE



**1. Clean the surface**  
Ensure you have a clean surface free from foreign material such as dust, stones, oil etc.



**2. Spray water & dry**  
Splash enough water on to a dry clean surface and allow to dry to improve the workability of the adhesive.



**3. Mix adhesive with water**  
Mix the adhesive 20 kg with approx. 6 lt of clean water. Stir gently using a low speed electric stirrer for good results.



**4. Apply adhesive**  
Apply the adhesive on the base **surface** or **wall** using a trowel.



**5. Fix tiles immediately**  
Fix the tiles immediately after applying the adhesive and press gently and firmly.



**6. Do grouting**  
Leave the tiles to bond for 24 hrs and then follow the grouting process carefully.

**NOTE:** This procedure is the same for all three products.

